



Motor Connctions



B+ 黄 Yellow B- 蓝 Blue

Brake Connctions



绿 Green 白 White

Common Rating

Step angle	18°
Position accuracy	18±0.09°
Dielectric strength	1000VAC 1min
Insulation resistance	100MΩhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max:0.02mm(Load 4.50g)
Axial play	Max:0.08mm(Load 900g)

Brake Specification

Voltage	24Vdc
Friction torque	4N·M

Specification

Current/phase	6.0 A
Voltage	3.2 V
DC Resistance/phase ±10%	0.53 Ω
Inductance/phase ±20%	3.9 mH
Holding torque	8 N·M
Inertia	2.8 kg·cm ²
Weight	3.8 kg

设计 Designed	日期 Date	材料 Material	深圳市雷赛智能控制股份有限公司 SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.
审核 Checked		第一角画法 First angle projection	混合式步进电机
批准 Approved		重量/Weight	86HSB85E
图号 Part No.		比例/Scale	
		阶段/Stage Mark	
		共 1 套 第 1 套 Sheet 1 of 1	
		图号 DWG. NO.	

版本/Rev	日期/Date	变更文件号/ECN NO.	变更内容/Revisions	设计/By